



# DECLARATION OF PERFORMANCE

## Fibrofor®

According Annex III of the Regulation (EU) No 574/2014  
Declaration No: Fibrofor Diamond 38, class Ia, 2016-775015

<b>Unique identification code of the product-type</b>	Fibrofor Diamond 38, class Ia, 2016-775015
<b>Intended use or uses</b>	For load bearing applications in concrete, mortar and grout
<b>Manufacturer</b>	Contec Fiber AG Via Innovativa 21 CH-7013 Domat/Ems
<b>Authorised representative</b>	No representative
<b>System/s of AVCP</b>	System 1
<b>Harmonized standard</b>	EN 14889-2:2006
<b>Notified body</b>	Technische Universität Darmstadt Institut für Werkstoffe im Bauwesen Karolinenplatz 5 DE-64289 Darmstadt identification number: 1343

### Declared performance

Essential characteristic	Performance	Harmonised technical specification
Tensile properties (tenacity)	> 400 N/mm <sup>2</sup>	EN 14889-2:2006
Effect on consistence (workability) of concrete	Consistence with 5 kg/m <sup>3</sup> fibers VEBE time: 7 s	
Influence on the strength of concrete	2.43 N/mm <sup>2</sup>	
Release of dangerous substances	NPD*	
Durability	-	

\* NPD = No performance determined

The performance of the product identified above is in conformity with the set of declared performance/s.

This declaration of performance is issued, in accordance with Regulation (EU) No. 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by

Robert Bader  
Business Line Manager

Domat/Ems, 27<sup>th</sup> January 2021

Signature

[http://www.contecfiber.com/media/declaration\\_of\\_performance\\_fibrofor\\_diamond\\_38-en.pdf](http://www.contecfiber.com/media/declaration_of_performance_fibrofor_diamond_38-en.pdf)